

MONO


POLY



**HELIENE**

**36<sup>M</sup>**

36-CELL MONOCRYSTALLINE MODULE



**180 Wp**

MAX POWER OUTPUT

**18.0%**

MODULE EFFICIENCY

**10 YEAR**

PRODUCT WARRANTY

**25 YEAR**

LINEAR PERFORMANCE GUARANTEE



GUARANTEED POSITIVE POWER SORTING: [-0 : +4.99 WP]



CERTIFIED FOR USE IN CLASS 1 DIVISION 2 HAZARDOUS LOCATIONS (GROUP A,B,C & D)



MANUFACTURED ACCORDING TO INTERNATIONAL QUALITY SYSTEM STANDARDS: ISO9001



40mm DOUBLE WEBBED FRAME ENSURES ROBUST AND RIGID PRODUCT FOR ALL INSTALLATION TYPES


HELIENE IS A PREMIER SOLAR MODULE MANUFACTURER, SERVICING THE GROWING SOLAR ENERGY MARKETS OF NORTH AMERICA.

COMBINING PROVEN EUROPEAN TECHNOLOGY WITH NORTH AMERICAN INGENUITY ALLOWS HELIENE TO MAKE A REAL COMMITMENT IN PROVIDING SMARTER ENERGY CHOICES FOR THE FUTURE.


**HELIENE**  
[www.heliene.com](http://www.heliene.com)

### LINEAR PERFORMANCE GUARANTEE



10 YEAR WORKMANSHIP WARRANTY • 25 YEAR LINEAR PERFORMANCE GUARANTEE



### DIMENSIONS FOR HELIENE 36M SERIES MODULES



### I-V CURVE FOR HELIENE 36M SERIES



### CERTIFICATIONS



### ELECTRICAL DATA (STC)

Peak Rated Power	$P_{mpp}$ (W)	180	175	170	165
Maximum Power Voltage	$V_{mpp}$ (V)	19.62	19.20	18.93	18.67
Maximum Power Current	$I_{mpp}$ (A)	9.30	9.22	9.11	8.98
Open Circuit Voltage	$V_{oc}$ (V)	23.79	23.40	23.29	23.03
Short Circuit Current	$I_{sc}$ (A)	9.74	9.63	9.50	9.37
Module Efficiency *	Eff (%)	18.0	17.5	17.0	16.5
Maximum Fuse Series Rating	MF (A)	20	20	20	20
Power Output Tolerance		[- 0 , + 4.99] Wp			

STC - Standard Test Conditions: Irradiation 1000 W/m<sup>2</sup> - Air mass AM 1.5 - Cell temperature 25 °C

\* Calculated using maximum power based on full positive output tolerance [-0 , +4.99] Wp

### MECHANICAL DATA

Dimensions (L x W x D)	1485 x 675 x 40 mm (58.6 x 26.6 x 1.6 inch)
Weight	14.5 kg (32 lbs)
Output Cables	*Optional
Junction Box*	IP65; 4 Terminal Screw Block; Terminals Compatible with 8 - 14 AWG Wire Compatible with PG 13.5 Cable Gland, M20 13mm (½") Conduit, or Other Cable Fittings for 6-12 mm <sup>2</sup> Cable
Frame	Double webbed 15 micron anodized aluminum alloy
Front Glass	Low-iron content, high-transmission PV solar glass
Solar Cells	36 Monocrystalline cells (156 x 156 mm)

\* Standard IP65 Junction Box with 800mm cables, Class 1 Div 2 Certification not applicable with this option

### CERTIFICATIONS

UL Listed	ULC/ORD-C1703-1, UL1703
IEC Listed	Optional

### TEMPERATURE RATINGS

Nominal Operating Cell Temperature (NOCT)	+45°C (±2°C)
Temperature Coefficient of $P_{max}$	-0.39%/°C
Temperature Coefficient of $V_{oc}$	-0.31%/°C
Temperature Coefficient of $I_{sc}$	0.045%/°C

### PACKAGING CONFIGURATION

Max Modules per box:	26 pieces
Max Modules per 53' trailer:	1560 pieces

### MAXIMUM RATINGS

Operational Temperature	-40°C - +85°C
Max System Voltage	600V

### WARRANTY

10 Year Manufacturer's Workmanship Warranty
25 Year Linear Power Guarantee
(Refer to product warranty page for details)